

Project Name	
Project #	
Model #	
Type	

FBA-U097-JLPC LED Series

FEATURES & SPECIFICATIONS

Intended Use: The JLPC series is an excellent choice for powerful and energy efficient lighting. These fixtures are made with aluminum bodies, a polycarbonate lens, and Epistar 2835 chips. The finish product has a refined and modern look with efficient LED technology to keep energy costs down while still providing excellent and long lasting lighting.

Installation: These luminaries are ideal for interior architectural and commercial applications. They are designed for illuminating pathways, walkways, stair wells, garages, etc.

Rating: IP40

Warranty: 5 years

Listings: ETL & DLC

View Angle: 110°

Lifetime: 50,000 hours

Fixture Material: White powder coated aluminum with polycarbonate lens.

Dimensions: (L x W x H Inch)

- JLPC2: 23 25/32 x 3 25/34 x 2 1/8
- JLPC4: 47 51/64 x 3 25/34 x 2 1/8
- JLPC5: 59 2/67 x 3 25/34 x 2 1/8
- JLPC8: 95 5/64 x 3 25/34 x 2 1/8



Optional functions pull chain ON OFF switch



- Lens: 100%UV stabilized Polycarbonate
- Non-breakable
- Excellent lumen output



ORDERING INFORMATION

EX: FBA-JLPC4-220-UNV-40K-SM-EM

Series	Wattage (Lumens)	Input Voltage	Color Temp	Sensor	Mounting	Emergency
1a. FBA-U097-JLPC2	2a. 210 (20W; 2,200lm)	3a. 27V	4a. 30K (3,000K)	5a. MS	6a. HM	7a. EM
1b. FBA-U097-JLPC4	2b. 220 (40W; 4,400lm)		4b. 40K (4,000K)	5b. Blank		7b. Blank (No EM)
1c. FBA-U097-JLPC5	2c. 230 (60W; 6,600lm)		4c. 50K (5,000K)			
1d. FBA-U097-JLPC8	2d. 240 (80W; 8,800lm)		4a. 60K (6,000K)			

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

3a. 100-277V input voltage

- 1a. 2ft
- 1b. 4ft
- 1c. 5ft
- 1d. 8ft

3a. 100-277Vac 50/60Hz

- 5a. Microwave Montion
- 5b. Leave Blank if not required

6a. Hanging Mount

- 7a. 90 Minutes battery
- 7b. Leave Blank if not required

1c. FBA-JLPC5

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21ST STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM