

| | |
|--------------|--|
| Project Name | |
| Project # | |
| Model # | |
| Type | |

FBA-U097-SOPC LED Series

FEATURES & SPECIFICATIONS

Intended Use: The SOPC series is an excellent choice for powerful and energy efficient lighting. These fixtures are made with aluminum housing. These luminaires offer great color uniformity and a prismatic polycarbonate diffuser for excellent lighting. The finish product has a refined and modern look with efficient LED technology to keep energy costs down while still providing excellent and long lasting lighting.

Installation: These luminaires are ideal for parking garages, stairwells, hallways, conference rooms, and other locations that require modern efficient light fixtures. These luminaires are great for new construction and retrofit projects.

Rating: IP20

Warranty: 5 years

Listings: ETL, DLC


View Angle: 120°

Lifetime: 50,000 hours

Fixture Body: Aluminum with a Non-Breakable, Non-discoloring, 100% UV Stabilized Polycarbonate lens.

Dimension:

- SOPC4: 47 3/64" L x 3 17/64" W x 3 21/32" H
- SOPC5: 58 11/32" L x 3 17/64" W x 3 21/32" H
- SOPC8: 93 15/16" L x 3 17/64" W x 3 21/32" H



ORDERING INFORMATION

EX: FBA-SOPC-220-UNV-50K-EM

| Series | Wattage (Lumens) | Input Voltage | Temperature | Mounting | Battery |
|--------------------|--------------------------|---------------|-----------------|------------------|------------------|
| 1a. FBA-U097-SOPC4 | 2a. 220 (40W; 4,400lm) | 3a. 27V | 4a. 30K (3000K) | 5a. SM (Surface) | 6a. Blank |
| 1b. FBA-U097-SOPC5 | 2b. 224 (50W; 5,500lm) | | 4b. 40K (4000K) | 5b. PC (Cable) | 6b. EM (Battery) |
| 1c. FBA-U097-SOPC8 | 2c. 230 (60W; 6,600lm) | | 4c. 50K (5000K) | 5c. PR (Rod) | |
| | 2d. 240 (80W; 8,800lm) | | | | |
| | 2e. 260 (120W; 13,200lm) | | | | |
| | 2f. 440 (160W; 17,700lm) | | | | |

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

1a. Available in 40W & 60W only

1b. Available in 50W & 60W only

1c. Available in 80W, 120W & 160W

3a. 100 - 277V input voltage

5a. Surface Mount 5b. Pendant Cable 5c. Pendant Rod

6a. leave blank if not needed 6b. 90 minute emergency battery; only available for 20W & 30W models

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes