

Project Name	
Project #	
Model #	
Туре	Under Canopy Option 4

FCP-U036-MASQ LED Series

FEATURES & SPECIFICATIONS

Intended Use: The MASQ series is an excellent choice for powerful and energy efficient lighting. These fixtures are made with die-cast aluminum bodies anodized with a bronze finish, a polycarbonate lens, and High Quality chips. The finish product has a refined and modern look with efficient LED technology to keep energy costs down while still providing excellent and long lasting lighting.

Installation: These luminaries are ideal for exterior architectural and commercial applications. They are designed for illuminating spaces adjacent to walls, such as pathways, walkways, courtyards, tunnels, garages, docks, bridges, parkways, gazebos, and gardens. Rating: Wet location

Warranty: 5 years

Listings: UL & cUL

View Angle: 120°

Lifetime: 50,000 hours

Fixture Body: Die-cast aluminum

Dimensions:

10.74" x 10.74" x 3.37"





ORDERING INFORMATION

A.

- Multiple installation ways
- 4KV surge protector
- Open air ventilation
- Heat dissipation
- Rust and corrosion proof
- Polyester powder coating



EX: FCP-RP03-040-27V-40K-DBR-CRL-MSN

Series	Wattage (Lumens)	Input Voltage	Temperature	DIM	Lens	Sensor	Finish	Emergency
1a. FCP-U036-MASQ	2a. 040 (40W; 5,100lm)	3a.27V	4a. 40K (4000K)	5a. Blank	6a.CRL	7a. (Blank)	8a. WHT	9a. (Blank)
			4b. 50K (5000K)	5b. DM	6b.FRL	7b. MSN		9b. (EM)
_		_	<u>.</u>			_		

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

3a. 100 - 277V input voltage5a. Leave Blank if not required5b. 0-10Vdc Dimming

- 6a. Clear lens6b. Frosted lens7a. Leave blank if not required
- 7b. Motion Sensor 8b. White (Powder Coated)
- 9a. Leave blank if not required9b. 90 Min Emergency

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM