

Project Name	
Project #	
Model #	
Туре	

FCP-U066-RP03 LED Series

FEATURES & SPECIFICATIONS

Intended Use: The RP03 series is an excellent choice for powerful and energy efficient lighting. These fixtures are made with die-cast aluminum bodies anodized with a bronze finish, a polycarbonate lens, and High Quality chips. The finish product has a refined and modern look with efficient LED technology to keep energy costs down while still providing excellent and long lasting lighting.

Installation: These luminaries are ideal for exterior architectural and commercial applications. They are designed for illuminating spaces adjacent to walls, such as pathways, walkways, courtyards, tunnels, garages, docks, bridges, parkways, gazebos, and gardens.

 Alinch threaded hole

 Strick threaded hole

lighting c facts



ORDERING INFORMATION

Rating: Wet location

Warranty: 5 years


Listings: UL & cUL

View Angle: 120°

Lifetime: 50,000 hours

Fixture Body: Powder coated die-cast aluminum with a polycarbonate lens.

Dimensions:













EX: FCP-RP03-045-27V-40K-DBR-CRL-MSN

	Series	Wattage (Lumens)	Input Voltage	Temperature	DIM	Lens	Sensor	Finish	Emergency
	1a. FCP-U066-RP03	2a. 030 (30W; 3,600lm)	3a. 27V	4a. 30K (3000K)	5a. Blank	6a.CRL	7a. (Blank)	8a. DBR	9a. (Blank)
		2b. 045 (45W; 5,000lm)		4b. 40K (4000K)	5b. DM	6b.FRL	7b. MSN	8b. WHT	9b. (EM)
1		2b. 060 (60W; 7,100lm)		4c. 50K (5000K)					
1				_		-		_	

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

3a. 100 - 277V input voltage5a. Leave Blank if not required5b. 0-10Vdc Dimming

6a. Clear lens6b. Frosted lens7a. Leave blank if not required

7b. Motion Sensor 8a. Dark Brown (Powder Coated 8b. White (Powder Coated) 9a. Leave blank if not required 9b. 90 Min Emergency

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

