

Project Name	
Project #	
Model #	
Type	

FDL-RD4-012-110-XXK-DM

AC110/120V (50/60Hz)

2700K/3000K/4000K/5000K/6000K

L107*W60*H41mm(D4.21*W2.36*H1.61 inch)

Ø120*44mm (D4 23/32 x H1 47/64 inch)

12W

>0.95

COB

>Ra80

Yes

Working Temperature: -20~50°C

38 Degree

25,000H

4 inch

900-960lm (\pm 5%)

Aluminum + PMMA Lens

Angle Adjustable Recessed LED Lighting Fixture (4 Inch)











DRIVER

Driver type: Isolated constant current driver

Input voltage: 110/120V AC Input current: 70mA Power Factor: 0.95 Power Efficiency: 85%

Specifications:

Item No.:

Input Voltage:

Power Factor:

Color Temperature:

LED Type:

Lumen Flux:

Beam angle:

Dimmable:

Lifespan:

Material:

Lamp Size:

Cut-out size:

Driver Box Size:

CRI:

Power:

Operating Temperature: -20~50°C

FEATURES

- Integrated fixture, easy installation, no trim and can required
- High quality cold forged aluminum heatsink, good heat dessipation
- 8 watts 750 lumens with high brightness COB light source
- Isolated constant current driver, works stable
- North American standard junction box inside, easy wiring
- Instant-on, no warm up time
- Free of harmful mercury, environment friendly
- 2700K to 6500K color temperature optional
- ETL/cETL approved
- Energy Star listed
- RoHS compliant
- 3 years warranty

*Dimmable 100%-5% smoothly when using triac dimmers Compatible dimmers include:

Lutron SCL-153P, DVCL-153P, CTCL-153P among others

CAUTIONS

- Rated for indoor use only; do not use where exposed to weather
- Do not use other drivers
- Do not connect multiple fixtures to one driver