

Project Name	
Project #	
Model #	
Type	

STANDARD



OPTIONAL



ILLUMINATION

- Long-life, efficient ultra-bright white LED.
- 5 watt LED per unit.
- Mirror-bright reflector and prismatic polycarbonate refractor.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power“ON”LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-diagnostic test feature continually diagnoses units performance and tests system to ensure reliable operation and to meet electrical and life safety codes.

MOUNTING

- Surface mount via easy connect back plate that fits most standard size junction boxes.
- Universal K/O pattern on back plate for wall mount.

HOUSING

- Decorative, low-profile, architectural design.
- Die-cast aluminum housing.
- Durable powder-coated finishes in white, black and dark bronze.
- Sealed and gasketed.


OPTIONS

- CW: Cold-weather unit for use in freezer applications. (in temperatures as low as (-20°C – 40°C)

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery pro-rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for wet locations. (0°C – 50°C)

DIMENSIONS



Sample Part Number: **DBEL-BR-SDT**

ORDERING INFORMATION

Model	Housing Color	Options	
DBEL	W White B Black BR Dark Bronze	SDT Self-diagnostics	CW Cold Weather

ELECTRICAL INFORMATION

Catalog Number	Input Watts (W)		Input Amps (A)	
	120V	277V	120V	277V
DBEL-SDT	2.7	2.8	0.026	0.012
DBEL-SDT-CW	2.9	3.0	0.031	0.014