

Project Name	
Project #	
Model #	
Type	

LED Edgelit



04-XEDU




ILLUMINATION

- Ultra-bright, energy efficient, long-lasting Red or Green LED
- UV-stabilized ultra-clear acrylic edgelit panel provided consistent, uniform illumination

WARRANTY

- Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

DIMENSIONS



FEATURES

- Energy efficient LED technology
- Decals & template provided for chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

MOUNTING

- Die-cast aluminum mounting canopy included—provides top, end or back mount convenience

OPTIONS

- SDT: Self-Diagnostic (option SDT) continually diagnoses unit's performance and tests system (auto battery discharge once every 30 days and once every 12 months) to ensure reliable operation and to meet electrical and life safety codes
- DC: Dual Circuit option on the AC-only unit enables it to be connected to two

at the same time (consult factory for more information on this)

- Edgelit EXIT panels available to order separately (contact customer service)
- Double face utilizes a silver or white mylar insert

ELECTRICAL

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- (1) Maintenance-free, rechargeable 4.8V 500mAh Ni-Cad battery (EM Model)
- Internal solid-state transfer switch automatically connects the internal battery to LED Board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

HOUSING

- Premium-grade, extruded aluminum housing (also available in black or white powder coated)

ORDERING INFORMATION

Model	Letter Color	Panel Color	Housing Color	Battery	Options	Face #
04-XEDU	R - Red G - Green	C - Clear M - Mirror (Silver Mylar) W - White (White Mylar)	W - White B - Black A - Anodized Aluminum	Blank - AC Only EM - NiCad Battery	SDT - Self Diagnostics 2C - Dual Circuit SW - Special Wording	1 - Single Face 2 - Double Face

AT