

Project Name	
Project #	
Model #	
Type	

FFB-U066-FR LED Series

Intended Use: The FFB-FR series is an excellent choice for powerful and energy efficient LED flood lighting. These fixtures are made of rugged aluminum housing with UV resistant powder coat finish offer outstanding corrosion protection. Glass lens. Vented housing isolated LED module maximizing product life and performance. Beautifully built fixture capable of meeting your outdoor lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: Facades, Wall Washing, Landscape, Bill Board & Building Lighting

Rating: IP66

Warranty: 5 years

Listings: UL, DLC



View Angle:

Fixture Body: Dark bronze powder coated die-cast aluminum, clear Tempered Glass Lens.


Mounting Hardware: 1/2 Knuckle.

Dimensions: (L x W)


- 6.84" x 5.97"



Luminous Intensity Distribution Curve



Luminous Intensity Distribution Curve



ORDERING INFORMATION

EX: FFB-FR-040-27V-50K-GM-NFL-DRB

Series	Wattage (Lumens)	Input Voltage	Temperature	Mounting	Beam Angle	Finish
1a. FFB-U-066-FR	2a. 020 (20W; 2,500lm)	3a. 27V	4a. 40K (4000K)	5a. GM	6a. NFL	7a. DRB
	2b. 030 (30W; 3,450lm)		4b. 50K (5000K)		6b. MFL	

Notes:

*If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

3a. 100-277V input voltage 5a. 1/2 Knuckle Mount

6a. N 20°

6b. M 40°

7a. Dark Bronze

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM