

Project Name	
Project #	
Model #	
Type	

FFL-U066-FD03 LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FFL-U066-FD03 series is an excellent choice for powerful and energy efficient LED flood lighting. These fixtures are made of rugged aluminum housing with UV resistant powder coat finish offer outstanding corrosion protection. UV Polycarbonate lens. Vented housing isolated LED module maximizing product life and performance. Beautifully built fixture capable of meeting your outdoor lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: Facades, Wall Washing, Landscape, Bill Board & Building Lighting

Rating: IP66



Warranty: 5 years

Listings: UL, DLC

View Angle:

Fixture Body: Dark bronze powder coated die-cast

aluminum, clear PC lens

Mounting Hardware: 1/2 Knuckle, Trunnion or

Wall mount

Dimensions: (W x H x D)

15W 30W 4.72x2.95x1.27in.

7.08x4.42x1.61in. (Knuckle & Trunnion)

(Knuckle & Trunnion & Wall mount)

8.26x5.15x2in.

(Knuckle & Trunnion & Wall mount)

45W

MOUNTING

1/2" Knuckle Mount Die-cast aluminum knuckle provides flexibilityin mounting from a variety of



Trunnion Mount

Die-cast aluminum trunnion is easily adapted to many surfaces and allows easy fixture aiming angles.



Wall Mount (30W & 45W)

Wall Mount is easy to install for direct wall mounting with 1/2' conduit wiring or standard J-box mounting













ORDERING INFORMATION EX: FFL-U066-FD03-045-27V-40K-KM-BLK

Series	Wattage (Lumens)	Input Voltage	Temperature	Mounting	Finish
1a. FFL-U066-FD03	2a. 015 (15W; 1,500lm)	3a. 27V	4a. 40K (4000K)	5a. KN	6a. BLK
	2b. 030 (30W; 3,000lm)		4b. 50K (5000K)	5b. TM	6b. DRB
	2a. 045 (45W; 5,400lm)			5c. WM	

*If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

3a. 100-277V input voltage 5a. 1/2 Knuckle Mount 5b. Trunnion Mount 5c. Wall Mount

6a. Black 6b. Dark Bronze

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes 1834 NW 21st STREET MIAMI. FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM

^{*}All of the products and specifications can change without prior notice*