

Project Name	
Project #	
Model #	
Type	

## PRODUCT DESCRIPTION

The suspended Up/down LED Luminaire is a commercial pendant lighting fixture utilizing an advanced LED optical system to achieve superior performance. The unique design is nearly transparent luminaire when off and excellent uniformity and efficiency when on, reaching 55% downlighting and 45% uplighting distribution, making the illusion of the light floating in mid-air, included UL Recognized constant current driver which support 0-10V dimming and step dimming, suitable for indoor lighting.

## PERFORMANCE SUMMARY

Efficacy: 105LPW
Delivered Light Output: 8400Lumens
Input Power: 80Watts
CRI: Ra>80
DLC CCT Options: 3500K/4000K/5000K
Input Voltage: 100-277V AC
Input current: 0.43A
THD: <20%
Power Factor: >0.9
Driver output: DC30-42V,0.88A
Standard Warranty: 5 Years
Standard Lifetime: Designed to L70 minimum 50,000 hours
Mounting: Suspended
Support to connect 5 pcs panels together in 120V AC support to connect 10 pcs panels together in 277V AC
Available 0-10v dimming and step dimming (100%,50%,10%-15%)
Signal Current: <2mA
Recommended Dimmers:DIVA-DVTV(LUTRON)
Dimensions: L 94.48" x W 7.87" x H 0.94"

## REGULATORY & VOLUNTARY QUALIFICATIONS

ETL	Yes
DLC	Pending
LM79 Report	Pending
Damp rated	Yes

## ORDER INFORMATION

EXAMPLE: FPD-D8-080-UNV-35K-DM

Product category	Size	Fixture wattage	Input Voltage	CCT(XX)	Dimming
FPD	D8=8'	080=80W	UNV= 100-277Vac	35=3500k 40=4000k 50=5000k	DM=0-10V

## Up/Down 8' LED Luminaires

