

Project Name	
Project #	
Model #	
Type	

FPD-U062-DE14 LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FPD-DE14 series is an excellent choice for powerful, energy efficient, and elegant pendant LED lighting. These fixtures have a unique design that is nearly transparent when off and offers excellent uniformity and efficiency. This fixture offers 65% down-light and 35% up-light distribution, creating an illusion of a light floating in mid-air.

Installation: These luminaires are ideal for residential and commercial applications. These lights are perfect for offices, meeting rooms, hallways, and other locations where elegant LED pendant lighting is required.

Rating: Damp locations

Warranty: 5 years

Listings: ETL

CRI: 80

Lifetime: 50,000 hours

Fixture Body: White powder coated aluminum trim with a clear (transparent when off) polymethyl methacrylate (PMMA) lens.

Dimensions:

- 47.24" L x 11.81" W x 1.06" H



ORDERING INFORMATION

EX: FPD-DE14-054-UNV-40K-DCD

Series	Wattage (Lumens)	Input Voltage	Temperature	Dimmable	Dimmable
1a. FPD-U062-DE14	2a. 054 (54W; 4,929lm)	3a. UNV	4a. 30K (3000K)	5a. SPD	6a. Blank
			4b. 35K (3500K)	5b. DCD	6b. EM
			4c. 40K (4000K)		
			4d. 50K (5000K)		

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

3a. 100 - 277V input voltage 5a. AC Step Dimming 5b. 0-10V DC Dimming 6a. Leave Blank if not required 6b. 90Minutes Em Pack (Mini Inverter)

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM