

Project Name	
Project #	
Model #	
Type	

FPL-U099-PR-LED Series

FEATURES & SPECIFICATIONS

The PR LED Round panel are 33/64" deep, Input voltage 120V AC, power consumption of 6, 12, 18 & 24 watts with 80+ CRI. Dimmable with widely available LED dimmers, Energy Star qualified, UL& FCC Listed. Are suitable for recessed installation using the clips or surface mounted installation which Mounts quickly and easily to 4" octagon, 4" round and 4" square junction boxes or retrofit installation, A variety of optional installation to simplify your projects.

Installation: These luminaires are ideal for hard ceiling, suspension and surface mounting.

IP Rating: IP20

Warranty: 5 years

Listings: ETL, Energy Star, FCC

CRI: >80


Fixture Body: Powder coated steel with a frosted polycarbonate lens.

Lifetime: 80,000 hours


Beam Angle: 120°

Dimensions:


- FPL-U099-PR06: 5 5/16" x 0 33/64"
- FPL-U099-PR07: 7 3/32" x 0 33/64"
- FPL-U099-PR09: 8 55/64" x 0 33/64"
- FPL-U099-PR12: 11 13/16" x 0 33/64"





- White
- Black
- Silver



A. J-Box installation is applied to 6W/12W/18W/24W mini panel for North American market



B. 5/6" Can is applied to 12W/18W/24W mini panel for North American market



Compatible J-box for surface mount



ORDERING INFORMATION EX: FPL-U099-PR09-18-USV-40K-WHT-DM

Series	Wattage (Lumens)	Input Voltage	Temperature	Finish	Dimmable	Battery
1a. FPL-U099-PR06	2a. 06 (6W; 510lm)	3a. USV	4a. 30K (3000K)	5a. WHT	6a. DM	7a. N/A
1b. FPL-U099-PR07	2b. 12 (12W; 1020lm)		4b. 40K (4000K)	5b. BKL		
1c. FPL-U099-PR09	2c. 18 (18W; 1,530lm)		4c. 50K (5000K)	5a. SVL		
1d. FPL-U099-PR12	2d. 24 (24W; 2,000lm)					

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

- 1a. FPL-U099-PR06 6 Watts
- 1c. FPL-U099-PR09 18 Watts
- 3a. 120V input voltage
- 5b. Black
- 6a. Triac Dimming
- 7a. No EM Available
- 1b. FPL-U099-PR07 12Watts
- 1d. FPL-U099-PR12 24 Watts
- 5a. White
- 5c. Silver

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM