

Project Name	
Project #	
Model #	
Type	

FRT-U115-R4S & B LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FRT-S & B series of LED down-light is an excellent choice for sleek modern new construction applications in which both style and energy efficiency are required. They are an excellent choice for offices, hospitals, classrooms, shopping centers, homes, and other commercial applications requiring low-lighting power density. These LED lights are a superior replacement to typical fluorescent lighting products because of their increased efficiency, longer life, and offer an elegance unmatched by any fluorescent products.

Installation: These luminaries are ideal for new construction flush lighting or retrofit applications.

Rating: Damp Location.

Warranty: 3 years

Listings: ETLus

CRI: 80

View Angle: 100°

Lifetime: 50,000 hours

Fixture Body: Powder coated aluminum trim with a frosted polycarbonate lens.

Dimension:



4" BAFFLED



5-6" BAFFLED



4" SMOOTH



5-6" SMOOTH



● ETL Listed

● Available in 4" & 5-6"

● Smooth & Baffled Trim

● Suitable for Damp Location

ORDERING INFORMATION

EX: FRD-U115-S4-010-USV-40K-ACD-WH

Series	Wattage (Lumens)	Input Voltage	Temperature	Dimmable	Finish	Mounting Hardware
1a. FRT-U115-R4B	2a. 010 (10W; 800lm)	3a. USV	4a. 27K (2700K)	5a. ACD	6a. WH	6a. (Blank)
1b. FRD-U115-R4S			4b. 30K (3000K)			6b. CLP
1c. FRD-U115-S5/6B	2b. 015 (15W; 1350lm)		4c. 35K (3500K)			
1d. FRD-U115-S5/6S			4d. 40K (4000K)			
			4e. 50K (5000K)			

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

1a. 4" Square Model
1b. 5" Round Model

3a. 120V 50/60Hz

5a. Triac Dimming

6a. White

7a. Leave Blank for box
7b. Can Hardware

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM