

Project Name	
Project #	
Model #	
Туре	

FSB-U023-ALG LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FSB-ALG series is an excellent choice for powerful and energy efficient site lighting. These fixtures are made with positive cooling technology to maximize the lifetime of the fixture. These fixtures are made with high quality chips to provide a long lasting, beautifully built fixture capable of meeting your site lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: These luminaries are ideal for parking lots, tennis courts, basketball courts, and other outdoor area lighting.

Rating: IP65


Warranty: 5 years


Listings: ETL, DLC 4.0



Light Distribution: TYPE III & V CRI: >80

Material: Die-cast Aluminum





ORDERING INFORMATION

EX: FSB-U023-ALG-200-UNV-50K-BLK-SF-T3

Series	Wattage (Lumens)	Input Voltage	Temperature	Options	Finish	Mounting	Dist TYPE
1a. FSB-U023-ALG	2a. 060 (60W; 7,800lm)	3a. UNV	4a. 30K (3000K)	5a. DCD	6a. BLK	7a. SF	8a. T3
	2b. 100 (100W; 13,000lm)	3b. HV	4b. 40K (4000K)	5b. PC		7b. PW	8b. T5
	2c. 150 (150W; 19,500lm)		4c. 50K (5000K)	5c. MS		7c. SA	
	2d. 200 (200W; 26,000lm)		4d. 57K (5700K)				
	2e. 240 (240W; 31,500lm)		· · ·				
	2e. 300 (300W; 39,000lm)						

Notes:

*If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

3a. 100 - 277V input voltage

3b. 347-480V input voltage

5a. 0-10V Dim (Standard)
5b. Photo Cell**
5c. Motion Sensor **
6a. Black

7a. Slip Fitter7b. Square/Round Pole, Wall Mount8b. Type 57c. Straight Arm

8a. Type 3

**Specify Voltage 120-277V, 347V or 480V

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

All of the products and specifications can change without prior notice

1834 NW 21st STREET MIAMI, FL 33142 | PHONE – 786.420.3600 | FAX – 786.420.3602 | SPECTRASOL-US.COM