

Project Name	
Project #	
Model #	
Type	

LED CEILING FIXTURE - DECO PUFF



- * Housing: Die-formed cold-rolled steel
- * Shade: High transmission acrylic creates excellent light distribution and uniformity
- * LED: High efficiency, high CRI, binned and mixed to reach uniform light
- * High power factor, low THD
- * 5 years warranty on driver and LED module
- * Certification: ETL / cETL, Energy Star



TYPE B



TYPE C

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (typ)	Dimension (OD x H)	Energy Star
2-0245D-B-xxxxK	120V	17W		> 80	1600	11.0" x 3.7"	YES
2-0246D-B-xxxxK	120V ~ 277V	24W	3000K/	> 80	2560	14.0" x 3.9"	YES
2-0247D-B-xxxxK	120V ~ 277V	35W	3500K/	> 80	3280	18.9" x 3.9"	--
2-0245D-C-xxxxK	120V	17W	4000K/	> 80	1600	11.0" x 4.5"	YES
2-0246D-C-xxxxK	120V ~ 277V	24W	5000K	> 80	2560	14.0" x 4.7"	YES
2-0247D-C-xxxxK	120V ~ 277V	35W		> 80	3280	18.9" x 4.7"	--

* Lumen (typ): Tested with 3000K CT

* Color Temperature Option (-xxxxK): 3000K, 3500K, 4000K, 5000K