

Project Name	
Project #	
Model #	
Type	

# FSM-U091 CEILING FIXTURE

- \* Housing: Die-formed cold-rolled steel
- \* Shade: High transmission acrylic or glass creates excellent light distribution and uniformity
- \* LED: High efficiency, high CRI, binned and mixed to reach uniform light
- \* High power factor, low THD
- \* 5 years warranty on driver and LED module
- \* Certification: UL / cUL, ETL / cETL, Energy Star



DC1505D



DC913D/DC916D



## LED TYPE

Model	Input Voltage	Input Wattage	LED CT /CRI	Lumen(typ)	Dimension (L x W x H)	Finish	Energy Star
DC913D-3000K	120V ~ 277V	21W	3000K / 80	1750	13.0" X 13.0" X 5.1"	Satin Nickel	YES
DC913D-4000K	120V ~ 277V	21W	4000K / 80	1850	13.0" X 13.0" X 5.1"	Satin Nickel	YES
DC916D-3000K	120V ~ 277V	35W	3000K / 80	2900	16.0" X 16.0" X 5.4"	Satin Nickel	YES
DC916D-4000K	120V ~ 277V	35W	4000K / 80	3000	16.0" X 16.0" X 5.4"	Satin Nickel	YES
DC1505D-3000K	120V ~ 277V	21W	3000K / 80	1750	13.0" X 13.0" X 3.8"	Satin Nickel	--
DC1505D-4000K	120V ~ 277V	21W	4000K / 80	1850	13.0" X 13.0" X 3.8"	Satin Nickel	--

\* More Color Temperature Option: 3500K, 5000K