

Project Name	
Project #	
Model #	
Type	

## FSM-U099-PR LED Series

### FEATURES & SPECIFICATIONS

**Intended Use:** The PR series of LED flush down-light is an excellent choice for sleek modern new construction applications in which both style and energy efficiency are required. They are an excellent choice for offices, hospitals, classrooms, shopping centers, homes, and other commercial applications requiring low-lighting power density. These LED lights are a superior replacement to typical fluorescent lighting products because of their increased efficiency, longer life, and offer an elegance unmatched by any fluorescent products. These down-lights are compatible with 4", 5", 6" & 8" existing recessed housings (with clips; retrofit applications) or 4" and 5" junction boxes (new construction applications)

**Installation:** These luminaries are ideal for new construction flush lighting or retrofit applications.

**Rating:** Damp Location

**Warranty:** 5 Year

**Listings:** UL & cUL

**CRI:** 80

**View Angle:** 100°

**Lifetime:** 50,000 hours

**Fixture Body:** Powder coated aluminum trim with a frosted polycarbonate lens.

**Dimension:**

PR12W	Φ 180x13mm
PR18W	Φ 225x13mm
PR24W	Φ 300x13mm
PS12W	162x162x15mm
PS18W	214x214x15mm
PS24W	289x289x15mm



### ORDERING INFORMATIONEX: FSM-U099-PR12-012-UNV-40K-DC-WH

Series	Wattage (Lumens)	Input Voltage	Temperature	Dimmable	Finish	Mounting Hardware
1a. FSM-U099-PR12	2a. 012 (12W; 1,000lm)	3a. UNV	4a. 30K (3000K)	5a. DC	6a. WH	7a. (Blank)
1b. FSM-U099-PR18	2b. 018 (18W; 1,500lm)		4b. 40K (4000K)			7b. CLP
1c. FSM-U099-PR18	2c. 024 (24W; 2,000lm)		4c. 50K (5000K)			
1d. FSM-U099-PS12						
1d. FSM-U099-PS18						
1d. FSM-U099-PS24						

Notes:

\*If you do not see an option you would like please inquire directly and we will work to accommodate your needs.\*

1a.PR Round Models 3a. 120V -277V 50/60Hz 5a. 0-10V Dimming 6a. White 7a. Leave Blank for J-box  
1b.PS Square Models 7b. Can Hardware

\*All of the products and specifications can change without prior notice\*

\*Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes\*