

Project Name	
Project #	
Model #	
Type	

FTP-U004-GRL LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FTP-U004-GRL series is an excellent choice for powerful and energy efficient site lighting. These fixtures are made with positive cooling technology to maximize the lifetime of the fixture. These fixtures are made with high quality SMD LED to provide a long lasting, beautifully built fixture capable of meeting your site lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: These luminaries are ideal for parking lots, Area Lighting, Parks, Walkways, and other outdoor area lighting.

Rating: IP65

Warranty: 5 years

Listings: UL

View Angle: 105 x 105


CRI: >75

Fixture Body: Die-cast Aluminum


Dimensions: (L x W x H)

17 3/4" (450)


NET WEIGHT (KG)



30W	5.8
50W	6.2
75W	6.5
100W	6.5



PHOTOMETRIC



ORDERING INFORMATION **EX: FTP-CL04-060-UNV-50K-BLK-PB**

Series	Wattage (Lumens)	Input Voltage	Temperature	Options	Finish	Mounting
1a. FTP-U004-GRL	2a. 030 (30W; 3,600lm)	3a. 27V	4a. 40K (4000K)	5a. MWS	6a. BK	7a. PB
	2b. 050 (50W; 6,000lm)	3b. 48V	4b. 50K (5000K)	5b. PHC	6b. WT	
	2c. 075 (75W; 9,000lm)			5c. Blank	6c. BZ	
	2d. 100 (100W; 12,000lm)					

Notes:

*If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

3a. 100 - 277V input voltage

5a. Motion Sensor (MWO) 5b. Photo Cell

7a. POLE BRACKET

3b. 347 - 480V input voltage 80W & 150W Model only

5c. Leave blank if not needed

6a. Black 6b. White 6c. Bronze

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

All of the products and specifications can change without prior notice