

Project Name	
Project #	
Model #	
Type	

FTP-U116-BL LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FTP-U116-BL series is an excellent choice for powerful and energy efficient site lighting. These fixtures are made with positive cooling technology to maximize the lifetime of the fixture. These fixtures are made with high quality SMD LED to provide a long lasting, beautifully built fixture capable of meeting your site lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: These luminaries are ideal for parking lots, Area Lighting, Parks, Walkways, and other outdoor area lighting.

Rating: IP65

Warranty: 3 years

Listings: UL




Fixture Body: Aluminum & PC/TUV

Dimensions: (L x W x H)

L W H
RF01: 12.99" x 5.24" x 28.54"

RF02: 12.99" x 5.24" x 32.48"

Line Drawing



ORDERING INFORMATION

EX: FTP-U116-BL-020-UNV-30K-B36-BK-360-PB

Series	Wattage (Lumens)	Input Voltage	Temperature	Pole	Finish	Distribution	Mounting	Emergency
1a FBL-U021-RF01	2a. 025 (25W; 3,400lm)	3a. 27V	4a. 30K (3000K)	5a. B28	6a. WH	7a. 60°	8a. BP	9a. Blank
	2b. 040 (40W; 5,400lm)		4b. 40K (4000K)		6b. BK			9b. EM
	2c. 060 (60W; 8,100lm)		4c. 50K (5000K)		6c. BZ			
1a FBL-U021-RF02	2d. 080 (60W; 10,600lm)			5b. B32	6d. GY			
	2e. 120 (120W; 16,200lm)							

Notes:

*If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

3a. 100 - 277V input voltage 5a. 28.54" 5b. 32.46" 6a. White 6b. Black 7a. 60° 8a. Base Plate 9a. leave Blank if not required
6c. Bronze 6d. Grey 9b. 90min EM (Remote)

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

All of the products and specifications can change without prior notice