

Project Name	
Project #	
Model #	
Type	

FTP-U116-BL LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FTP-U116-BL series is an excellent choice for powerful and energy efficient site lighting. These fixtures are made with positive cooling technology to maximize the lifetime of the fixture. These fixtures are made with high quality SMD LED to provide a long lasting, beautifully built fixture capable of meeting your site lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.


Installation: These luminaries are ideal for parking lots, Area Lighting, Parks, Walkways, and other outdoor area lighting.

Rating: IP65

Warranty: 3 years

Listings: UL

Fixture Body: Aluminum & PC / TUV **Dimensions:** (L x W x H)














360° Distribution 180° Distribution



ORDERING INFORMATION

EX: FTP-U116-BL-020-UNV-30K-B36-BK-360-PB

Series	Wattage (Lumens)	Input Voltage	Temperature	Pole	Finish	Distribution	Mounting	Emergency
1a. FTP-U116-BL	2a. 010 (10W; 900lm)	3a. 27V	4a. 30K (3000K)	5a. B12	6a.WH	7a. 18	8a. PB	9a. Blank
	2b. 020 (20W; 1,800lm)		4b. 40K (4000K)	5b B24	6b.BK	7b. 27		9b. EM
	2c. 030 (30W; 2,700lm)		4c. 50K (5000K)	5c.B36		7c.36		
				5D.B42				

3a. 100 - 277V input voltage 5a. 12" 5b. 24" 5c. 36" 6a. White 6b. Black (Standard) 5d. 42" (Special order)

7a. 180° 7b. 270° 7c. 360° 7a. Pole

9a. leave Blank if not required 9b. 90min EM

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

^{*}If you do not see an option you would like please inquire directly and we will work to accommodate your needs. *

^{*}All of the products and specifications can change without prior notice*