

Project Name	
Project #	
Model #	
Туре	

FWP-U066-SMD LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FWP-SMD series is an excellent choice for powerful and energy efficient small wall packs with an option for a built-in photocell. These small series wall packs are perfect for security locations, storage, perimeter areas, entry ways, and residential exteriors.

Installation: These luminaires are ideal for outdoor pathway lighting.

Rating: Wet location

Warranty: 5 years

Listings: UL

Lifetime: 50,000 hours

View Angle: 180°

CRI: 80

Fixture Body: Powder coated aluminum with a polycarbonate lens.

7a. leave blank if not required

7b. Photocell

Dimensions:

8.38" L x 5.48" W x 3.5" H





ORDERING INFORMATION EX: FWP-SMD-025-UNV-40K-WHT-CRL-PHC

Series	Wattage (Lum	Input Voltage	Temperature	Finish	Lens	Sensor
1a. FWP-U066-SMD	2a. 015 (15W; 1,500lm)	3a. UNV	4a. 40K (4000K)	5a. WHT	6a. CRL	7a. (Blank)
	2b. 017 (17W; 1,700lm)	3b. USV	4b. 50K (5000K)	5b. DBR	6b. FRL	7b. PHC
	2c. 025 (25W; 2,200lm)					

N	otes:
11	otes.

If you do not see an option you would like please inquire directly and we will work to accommodate your needs. 5b. Dark Bronze

3a. 100 - 277V input voltage

3b, 120V input voltage 5a. White; powder coated

- 6a. Clear lens 6b. Frosted lens
- *All of the products and specifications can change without prior notice*

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes

1834 NW 21st STREET MIAMI, FL 33142 | PHONE - 786.420.3600 | FAX - 786.420.3602 | SPECTRASOL-US.COM