

Project Name	
Project #	
Model #	
Type	

LED WALL SCONCE FWS-U091-W & MDF SERIES

- * Housing: Die-formed cold-rolled steel
- * Shade: High transmission acrylic or glass creates excellent light distribution and uniformity
- * LED: High efficiency, high CRI, binned and mixed to reach uniform light
- * High power factor, low THD
- * LED CRI: > 80
- * 5 years warranty on driver and LED module
- * Certification: ETL / cETL, Energy Star



W199D



MDF039D



W194D



W280D

Model	Input Voltage	Input Wattage	LED CT	Lumen (typ)	Finish	Dimension (W x H x D)	Energy Star
W199D-xxxxK-62	120V ~ 277V	14W	3000K	1400	Satin Nickel	16.8" x 8.5" x 4.0"	YES
MDF039D-xxxxK-62	120V ~ 277V	14W	3000K	1360	Satin Nickel	16.0" x 7.9" x 4.0"	YES
W194D-xxxxK-62	120V ~ 277V	15W	3000K	700	Satin Nickel	12.5" x 4.5" x 3.6"	--
W280D-xxxxK-05	120V	18W	3000K	1470	Black	11.5" x 8.1" x 9.5"	--

- * Lumen (typ): Tested with 3000K CT
- * Finish Option: -62 Satin Nickel, -30 Oil Rubbed Bronze
- * More Color Temperature Option: 3500K, 4000K, 5000K

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes