

| | |
|--------------|--|
| Project Name | |
| Project # | |
| Model # | |
| Type | |

FWS-U107-UPD LED Series

FEATURES & SPECIFICATIONS

Intended Use: The FWS-UPD series is an excellent choice for powerful, low profile, and energy efficient wall packs. These fixtures are made with high quality LED's, an aluminum body with a polycarbonate lens, and a powder coating finish to provide a long lasting, low profile, and beautifully built fixture capable of meeting your wall pack lighting needs. The wide range of wattages ensure that there's a lighting option for any application you have.

Installation: These luminaires are ideal for outdoor lighting, site lighting, stairwells, and parking garages.

Rating: IP65

Warranty: 5 years

Listings: ETL

Lifetime: 50,000 hours

View Angle: 15°, 30°, 60°, 90°

Fixture Body: Powder coated die-cast aluminum.

Dimensions:

- 5X2S : 9 1/16 H x 4 21/64 W x 2 9/16D
- 6X2S : 9 1/16 H x 4 21/64 W x 2 9/16D

FWS-UPD-5X2S



FWS-UPD-6X2S



ORDERING INFORMATION

EX: FWS-UPD-5X2S-UNV-40K-15-GY

| Series | Wattage (Lumens) | Input Voltage | Temperature | Beam Angle | Finish |
|-------------|-------------------------|---------------|-----------------|------------|-----------------|
| 1a. FWS-UPD | 2a. 5X2S (10W; 1,000lm) | 3a. UNV | 4a. 30K (3000K) | 5a. 15° | 6a. WH (White) |
| 1b. FWS-UPD | 2b. 6X2S (12W; 1,200lm) | | 4b. 40K (4000K) | 5a. 30° | 6b. GY (Grey) |
| | | | 4c. 50K (5000K) | 5a. 60° | 6c. RD (Red) |
| | | | | 5a. 90° | 6d. YM (Yellow) |
| | | | | | 6e. BL (Blue) |
| | | | | | 6f. GR (Green) |
| | | | | | 6g. BK (Black) |

Notes:

If you do not see an option you would like please inquire directly and we will work to accommodate your needs.

3a. 100 - 277V input voltage 6a. White & 6g. Black are options with minimum quantities.

All of the products and specifications can change without prior notice

Please note this specification sheet is considered to be business promotional material and not used for product listing identification purposes